

Warranty

ISO 9001 Quality Management

The TempArmour® Freezer Advantage

- Superior temperature stability and uniformity
- Temperature stays within -50°C to -15°C (-58°F to +5°F) range up to 4 days when power cut (no batteries required)
- Meets CDC and VFC Vaccine Program Requirements and Recommendations

- Comprehensive vaccine organization system
- Exceptionally low power consumption
- No scheduled maintenance required
- Pharmaceutical grade

SPECIFICATIONS

	Holds over 100 boxes of 10 x 0.5 ml vials
Capacity	(based on typical manufacturer box sizes).
PHYSICAL SPECS:	
External Freezer Dimensions	26.5 x 25 x 31 in
(W x L x H)	67.3 x 63.5 x 78.7 cm
Internal Basket Dimensions	12 x 8 x 10 in
(W x L x H)	
Weight	155 lbs
Cabinet	Chest Style; Corrosion-resistant coated steel exterior; 6 ft cord; lock
Refrigerant	Refrigerant R600a (an environmentally friendly non-toxic refrigerant)
TEMPERATURE MONITORING:	
Data Logger	Certified and Calibrated to ISO 17025; 2 year calibration
Data Logger	VFC Compliant
Min-Max Thermometer	Certified and Calibrated to ISO 17025
Willi-Wax Mel Mometer	VFC Compliant
POWER SPECIFICATIONS:	
Energy Source (AC)	110-120 V 60 Hz
Power Consumption	20 W/hr
OTHER:	

2 year parts & service; 5 year compressor

Manufactured in an ISO 9001 Certified Facility